

Photoinduced Ring Opening Copolymerization of Perfluoropolyalkylethers

Original

Photoinduced Ring Opening Copolymerization of Perfluoropolyalkylethers / Trusiano, Giuseppe; Bonneaud, Céline; Burgess, Julia; Rizzello, Melania; Vitale, Alessandra; Joly-Duhamel, Christine; Friesen, Chadron M.; Bongiovanni, ROBERTA MARIA. - STAMPA. - (2018). (Intervento presentato al convegno The 5th European Symposium of Photopolymer Science tenutosi a Mulhouse, France nel September 3-6, 2018).

Availability:

This version is available at: 11583/2712968 since: 2018-09-13T17:43:06Z

Publisher:

Nessuno

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Photoinduced Ring Opening Copolymerisation of Perfluoropolyalkylethers

Giuseppe Trusiano¹, Céline Bonneaud², Julia Burgess³, Melania Rizzello¹, Alessandra Vitale¹, Christine Joly-Duhamel², Chadron M. Friesen³, Roberta Bongiovanni¹

¹Department of Applied Science and Technology, Politecnico di Torino, 10129 Torino, Italy

²Institut Charles Gerhardt, UMR CNRS 5253, Ecole Nationale Supérieure de Chimie de Montpellier, 34296 Montpellier Cedex 5, France

³Department of Chemistry, Trinity Western University, Langley, British Columbia V2Y 1V1, Canada

INTRODUCTION


Perfluoropolyalkylethers (PFAEs), based on structural units such as $-(CF_2O)-$, $-(CF_2CF_2O)-$, $-(CF_2CF_2CF_2O)-$ and $-(CF(CF_3)CF_2O)-$, represent a special class of fluoropolymers with remarkable properties (low glass transition temperature, high chemical and thermal inertness, low surface energy and refractive index, excellent ageing, weather and flame resistances)[1]. They can be a non-toxic alternative to the long perfluoroalkyl chains presently banned in many countries[2], and be used in many high technology areas such as aerospace, aeronautic (seals, gaskets), automotive industry, microelectronics, optics or even for antifouling and release coatings or textile treatment.

The purpose of our work is to synthesize new PFAEs by anionic ring-opening polymerization of hexafluoropropoxide (HFPO) and functionalize them with different reactive groups. Here we describe the synthesis of PFAE monofunctional alcohols (HFPO_n-MA) with different molecular weight and their use in photoinduced ring-opening polymerization of non-fluorinated diepoxides.


The bulk properties of the UV-cured copolymers were practically unaffected by the presence of the fluorinated comonomers when added in low amount (less than 5%wt), but their addition reflected on the surface properties, that were strongly modified.

SYNTHESIS OF HFPO_n-MA


► ANIONIC RING-POLYMERIZATION OF HEXAFLUOROPROPYLENE OXIDE (HFPO)



► FUNCTIONALIZATION OF HFPO OLIGOMERS



► GENERAL PROPERTIES OF HFPO_n-MA




$n = 5, M_n = 1150$

$n = 10, M_n = 1810$


- Stability from -75 °C to 350 °C
- No formation of volatile products
- Excellent chemical stability

PHOTOPOLYMERIZATION & CHARACTERIZATION




FT-IR CONVERSION CURVES




$I = 300 \text{ mW cm}^{-2}$ film thickness = 10 μm Oxirane IR band at 910 cm⁻¹



By adding the HFPO-MA, the reaction speeds up, the oxirane ring conversion is higher confirmed by photo-DSC. Highly crosslinked polymeric networks are obtained whose gel percentage is higher than 92%



At the surface the HDGE polymer is modified by HFPO_n-MA: air surfaces are made both hydrophobic and oleophobic, while glass surfaces are hydrophilic and oleophobic [3]. Air surfaces are oil and solvent repellent; they are self-cleaning.



CHARACTERIZATION OF HFPO_n-MA



► ¹H-NMR (400 MHz, DMSO-d₆, 25 °C)

- δ :
- 3.66 (s-broad, -CF(CF₃)CH₂OH, 1H)
 - 3.45 (d, -CF(CF₃)CH₂O-, 2H, ³J_{H-F} = 14.8 Hz)

► ¹⁹F-NMR (400 MHz, BENZENE-d₆, 25 °C)

- δ :
- 146.04 (q, CF(CF₃) of repeat unit)
 - 137.67 (ω CF(CF₃))
 - 131.53 (s, α CF₂)
 - 84.34 to -80.01 (CF₃ and CF₂ of repeat unit)

► GC/MS (70 eV)



$$n = \int CF_{-145.41} = 5 \text{ (or } 10)$$

$$M_n = \text{mass of } \alpha \text{ unit} + n \times \text{mass of repeat unit} + \text{mass of } \omega \text{ unit}$$

$$M_n = 185 + n \times 166 + 131 = 1146 \text{ HFPO}_5\text{-MA}$$

$$1810 \text{ HFPO}_{10}\text{-MA}$$

ACKNOWLEDGMENTS

This project has received funding from the Horizon 2020 European Union's Research and Innovation Program under grant agreement No. 690917



REFERENCES

- [1] R. Bongiovanni, A. Medici, A. Zompatori, S. Garavaglia, C. Tonelli Perfluoropolyether polymers by UV curing: Design, synthesis and characterization Polym. Int., vol. 61, no. 1, pp. 65–73, 2012.
- [2] Z.Wang, J.C. DeWitt, C.P.Higgins, I.T.Cousins A Never-Ending Story of Per- and Polyfluoroalkyl Substances (PFASs) Environ. Sci. Technol. vol. 51, pp.2508–2518, 2017.
- [3] Y.Wang et al. Effect of end-groups on simultaneous hydrophilicity/oleophobicity and antifogging performance of nanometer thick PFPE films RCS Adv. vol.5, pp. 30570- 30576, 2015.